

Jumper Cables



1/2" Superflexible Foam Dielectric Cable



PRODUCT FEATURES

- No need for tape or other external weatherproofing
- IP68-classified and water-pressure proof tested down to 25 m
- Designed to maintain high pressure on contact surfaces to reduce intermodulation
- Each cable individually tested and labelled with return loss graph, 0 - 2.2 GHz
- 10-year comprehensive warranty

COMMON FOR ALL

CABLE TYPE	1/2" Superflex
FREQUENCY RANGE	0 - 5 GHz
VSWR / RETURN LOSS	
0 - 2.2 GHz	1.08 / -28 dB
0 - 3.5 GHz	1.08 / -28 dB*
INTERMODULATION**	
2 x 20 W transmitter	< -156 dBc
OPERATING TEMPERATURE	-55 °C to +80 °C

DIN 7/16 TO DIN 7/16

ARTICLE	CONNECTORS	LENGTH	PIECES IN BOX
JBBO-S012-AB05	DIN 7/16 male to DIN 7/16 male	0.5 m (1.64 ft)	25
JBBO-S012-AB10	DIN 7/16 male to DIN 7/16 male	1.0 m (3.28 ft)	25
JBBO-S012-AB20	DIN 7/16 male to DIN 7/16 male	2.0 m (6.56 ft)	20
JBBO-S012-AB25	DIN 7/16 male to DIN 7/16 male	2.5 m (8.20 ft)	15
JABO-S012-AB15	DIN 7/16 female to DIN 7/16 male	1.5 m (4.92 ft)	25
JABO-S012-AB30	DIN 7/16 female to DIN 7/16 male	3.0 m (9.84 ft)	15

* Typical performance for jumpers of ordinary length.

** During intermodulation measurement attached cables are exposed to shock and vibration.