

# PDU

(Power Distribution Unit)



## PRODUCT FEATURES

- Individual channel alarms
- Individual channel LED monitor

ARTICLE	EXT -30201	EXT-30202
<b>ELECTRICAL</b>		
<b>INPUT VOLTAGE</b>	20 - 60 V DC, positive or negative	20 - 60 V DC, positive or negative
<b>INPUT POLARITY PROTECTION</b>	Yes	Yes
<b>OUTPUT VOLTAGE</b>	12 V DC	12 V DC
<b>OUTPUT PROTECTION</b>	Over current and over voltage	Over current and over voltage
<b>NUMBER OF SUPPORTED TMA PORTS</b>	6	2
<b>ALARM</b>	Three pin alarm with NC and NO contacts individual LED indicator	Three pin alarm with NC and NO contacts individual LED indicator
<b>ENVIRONMENTAL AND STANDARDS</b>		
<b>TEMPERATURE</b>	-10 to +65 °C	-10 to +65 °C
<b>EMC</b>	EN 301 498-8	EN 301 498-8
<b>ENVIRONMENTAL</b>	EN 300 019	EN 300 019
<b>SAFETY</b>	EN 60 590	EN 60 590
<b>INGRESS PROTECTION</b>	IP20	IP20
<b>MECHANICAL</b>		
<b>DIMENSIONS, WALL MOUNT</b>		
(W x H x D)	218 x 125 x 43.5 mm	218 x 125 x 43.5 mm
<b>1U 19" RACK MOUNT OPTIONAL</b>		
<b>WEIGHT</b>	500 g	500 g
<b>CONNECTORS</b>	CIN 6 x SMB Male DC Molex Microfit 2 x 2 Alarm Molex Microfit 1 x 3	CIN 6 x SMB Male DC Molex Microfit 2 x 2 Alarm Molex Microfit 1 x 3